

RESPIRATORY GEAR

HORIZONTAL FLAT FOLD P2 RESPIRATOR WITH VALVE

PRODUCT DATA SHEET: PC5025



PRODUCT CODE:
PC5025



FEATURES AND BENEFITS

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P2 disposable respirator for protection against mechanically & thermally generated particles.
- Dual latex free elastic straps for ease of donning & doffing.
- Horizontal flat fold for improved comfort & fit.
- Adjustable nose bridge and soft inner nose foam for ultimate comfort and fit.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Easily worn with glasses & goggles.
- Resealable bag for hygienic storage.

AVAILABLE IN

PRODUCT CODE	MOQ	PACK QUANTITY	CARTON QUANTITY
PC5005	1 box	10 pieces	20 boxes

PRODUCT DETAILS

Straps:	Latex-Free Rubber Band
Nose Foam:	EVA
Nose Clip:	PP + STEEL
Filter Media:	Polypropylene Melt-Blown
Weight:	14.45g ± 1

CARE INSTRUCTIONS

Shelf life of the unopened product is 3 years from date of manufacture when stored within temperature range of -20°C to +25°C & less than 80% relative humidity.

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

Ensure mask is correctly fitted prior to each use & conduct annual fit testing in accordance with AS/NZS 1715:2009.



WARNINGS AND USE LIMITATIONS

1. Facial hair has the potential to compromise the required protective seal of the respirator.
2. Ensure adequate oxygen levels are present.
3. Ensure the contamination is known and the respirator is suitable for the application.
4. Replace when taste, smell or the breathing resistance is high.
5. Store in a clean resealable storage device.

STANDARDS

CERTIFIED TO:

AS/NZS 1716:2012 Respiratory Protective Devices
Certified by SAI Global

To be used in conjunction with: AS/NZS 1715:2009 -
Selection, use & maintenance of respiratory protective
equipment



CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1µm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

AUSTRALIA:
1800 770 723
INFO@PROCHOICESAFETYGEAR.COM

NEW ZEALAND:
0800 888 778
INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM

